



INCLUDES

• Cap

UNIQUE FEATURES

- All-plastic design
- More than 1 turn of thread engagement
- · Variety of graphics available
- Non-vented
- Low profile

REASONS TO CHOOSE

- Proven performance
- Long-lasting durability
- Ideal for high-volume applications
- Common thread size
- Mega grip for easy handling
- Economical



Revised 7/25

Disclaimer: At Kelch, we make quality products. We do not know how you will use our product. You, the customer, are in the best position to know the uses and conditions to which our products will be subjected and to know how our product will perform in your application.

You are responsible for identifying and performing tests necessary to assure that our product is safe and suitable for the application you have choosen. We ask that you hold us harmless from any claims that result from our product being used in an unsafe or unsuitable way.









COMPOSITION


- Engineered thermoplastics
- All-plastic cap designed for use in corrosive environments
- Non-vented cap

THREAD SIZE

- 2 1/4" modified buttress thread with 5 threads per inch
- Modified buttress thread allows for expansion and contraction of filler neck

FILLER NECK SPECIFICATIONS

- Injection molding/blow molding
 - Kelch Print 1407
- · Rotational molding
 - Kelch Print 6319



Revised 7/25

Disclaimer: At Kelch, we make quality products. We do not know how you will use our product. You, the customer, are in the best position to know the uses and conditions to which our products will be subjected and to know how our product will perform in your application.

You are responsible for identifying and performing tests necessary to assure that our product is safe and suitable for the application you have choosen. We ask that you hold us harmless from any claims that result from our product being used in an unsafe or unsuitable way.

MOLDED-IN GRAPHICS

Options include:

· Custom molded-in graphics

GASKET OPTIONS

- Nitrile
- FKM

PAD PRINTING OPTIONS FOR CAPS

· Standard and custom pad printing available







5208