

REMOTE GAUGE

INCLUDES

Gauge

UNIQUE FEATURES

- Hermetically sealed and isolated from the fluids
- Most compact gauge available
- Colored, highly-visible indicator
- Available with pipe threads or with press fit
- Multiple graphics options

REASONS TO CHOOSE

- Proven performance
- Long-lasting durability
- Remote access reading
- Low profile, compact
- Permanent mount







REMOTE GAUGE

COMPOSITION

- Engineered thermoplastics
- For use on plastic or metal reservoirs
- Stainless steel frame and Helix

MOUNTING

- Request Kelch print #7038 for recommended hole size and wall thickness specification
- Thread-in 1.00" 11.5 NPSM thread with O-ring. Request Kelch print #4071 for recommended tank geometry
- Kelch sells a driver 204052 for installation of threaded Multi-Level gauge

GAUGE LENGTH OPTIONS

- Gauge in lengths of 5" 24", in ½" increments
- Gauge length to be minimum $\frac{1}{2}$ " less than the depth of tank

GROMMET OPTIONS (SOLD SEPARATELY)

- Nitrile pt. #203882
- FKM pt. #203883

INDICATOR OPTIONS

- · Standard color red
- Kelch standard red and yellow colors available

DIAL OPTIONS

• Standard and custom graphics available






6508

6509

CROSS SECTION VIEW



Revised 7/22

Disclaimer: At Kelch, we make quality products. We do not know how you will use our product. You, the customer, are in the best position to know the uses and conditions to which our products will be subjected and to know how our product will perform in your application.

You are responsible for identifying and performing tests necessary to assure that our product is safe and suitable for the application you have choosen. We ask that you hold us harmless from any claims that result from our product being used in an unsafe or unsuitable way.



FOR MORE INFORMATION, CALL A KELCH
REPRESENTATIVE TODAY AT **877.944.5699 • KELCH.COM**©2022 0B7472005